U.S. Patent Application No.: Unknown

March 2, 2005

Page 5 of 10

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in

the application:

LISTING OF CLAIMS:

Claims 1-7 (canceled).

Claim 8 (new): A monolithic ceramic electronic component comprising:

a first element portion including a laminate of ceramic layers and internal

electrodes; and

a second element portion including a laminate of ceramic layers and internal

electrodes; wherein

at least the first element portion and the second element portion are stacked to

define a ceramic laminate, and a porosity of the ceramic layers of the first element

portion is different from a porosity of the ceramic layers of the second element portion.

Claim 9 (new): The monolithic ceramic electronic component according to Claim

8, wherein the first element portion includes a first coil defined by the internal electrodes

thereof being electrically connected together, the second element portion includes a

second coil defined by the internal electrodes thereof being electrically connected

together, and the first coil and the second coil are electrically connected to define an

inductor.

Claim 10 (new): The monolithic ceramic electronic component according to Claim

8, wherein the first element portion includes a coil defined by the internal electrodes

U.S. Patent Application No.: Unknown

March 2, 2005 Page 6 of 10

thereof being electrically connected together, the second element portion includes a

capacitor in which any two adjacent electrodes are separated by a ceramic layer, the

porosity of the ceramic layers of the second element portion is lower than the porosity of

the ceramic layers of the first element portion, and the coil and the capacitor are

electrically connected to define an LC filter.

Claim 11 (new): The monolithic ceramic electronic component according to Claim

8, wherein the ceramic layers of the first element portion and the ceramic layers of the

second element portion are made of the same ceramic material.

Claim 12 (new): The monolithic ceramic electronic component according to Claim

8, wherein the ceramic layers of the first element portion are made of

low-permeability ceramic green sheets and the ceramic layers of the second element

portion are made of high-permeability ceramic green sheets.

Claim 13 (new): The monolithic ceramic electronic component according to Claim

8, wherein the ceramic layers of the first element portion have a relatively small number

of pores and the ceramic layers of the second element portion have a relatively large

number of pores.

Claim 14 (new): The monolithic ceramic electronic component according to Claim

8, wherein the first element portion has a high permeability and a high dielectric

constant, and the second element portion has a low permeability and a low dielectric

constant.

U.S. Patent Application No.: Unknown

March 2, 2005

Page 7 of 10

Claim 15 (new): The monolithic ceramic electronic component according to Claim

9, wherein an inductance of the first coil in the first element portion is lower than an

inductance of the second coil in the second element portion.

Claim 16 (new): The monolithic ceramic electronic component according to Claim

9, wherein a stray capacitance formed in parallel with the first coil of the first element

portion is smaller than a stray capacitance formed in parallel with the second coil of the

second element portion.

Claim 17 (new): The monolithic ceramic electronic component according to Claim

8, wherein a resonant frequency of the first element portion is higher than a resonant

frequency of the second element portion.

Claim 18 (new): The monolithic ceramic electronic component according to Claim

9, wherein a winding direction of the first coil is opposite to that of the second coil.

Claim 19 (new): The monolithic ceramic electronic component according to Claim

8, wherein the porosity of the first element portion is about 30% to about 80% and the

porosity of the second element portion is about 10% or less.

Claim 20 (new): The monolithic ceramic electronic component according to Claim

8, wherein the porosity of the first element portion is about 20% and the porosity of the

second element portion is about 60%.

U.S. Patent Application No.: Unknown

March 2, 2005

Page 8 of 10

Claim 21 (new): The monolithic ceramic electronic component according to Claim

8, wherein the monolithic ceramic electronic component is one of a monolithic inductor,

a monolithic impedance component, a monolithic LC filter, a monolithic capacitor, and a

monolithic transformer.

Claim 22 (new): A method for making a monolithic ceramic electronic component

comprising:

stacking ceramic layers and internal electrodes to form a first element portion;

stacking ceramic layers and internal electrodes to form a second element portion;

and

stacking at least the first element portion and the second element portion to form

a ceramic laminate; wherein

an amount of a granular evaporative pore-forming agent incorporated into a

ceramic slurry for forming the ceramic layers of the first element portion is different from

an amount of the granular evaporative pore-forming agent incorporated into a ceramic

slurry for forming the ceramic layers of the second element portion so that the first

element portion and the second element portion have different porosities of ceramic

layers.

Claim 23 (new): The method according to Claim 22, wherein either the ceramic

slurry for forming the ceramic layers of the first element portion or the ceramic slurry for

forming the ceramic layers of the second element portion is not incorporated with the

granular evaporative pore-forming agent.

U.S. Patent Application No.: Unknown

March 2, 2005 Page 9 of 10

Claim 24 (new): The method according to Claim 22, wherein the ceramic slurry

for forming the ceramic layers of the first element portion and the ceramic slurry for

forming the ceramic layers of the second element portion comprise the same ceramic

material.

Claim 25 (new): The method according to Claim 22, wherein the porosity of the

first element portion is about 30% to about 80% and the porosity of the second element

portion is about 10% or less.

Claim 26 (new): The method according to Claim 22, wherein the porosity of the

first element portion is about 20% and the porosity of the second element portion is

about 60%.

Claim 27 (new): The method according to Claim 22, wherein the monolithic

ceramic electronic component is one of a monolithic inductor, a monolithic impedance

component, a monolithic LC filter, a monolithic capacitor, and a monolithic transformer.